MSDS - Material Safety Data Sheet

Product Name: Soldering Paste

MSDS No.: 097250 Part Numbers Covered: 097205-12 097220-12 097405 097507 097205-48 097225-144 097406 097508 097206 097225-6 097455-12 097509 097208-48 097225-C 097455-D 097511 097210-12 097250 097460 097516 097300-6 097212-12 097500 097517 097215-12 097301-6 097505 097518 097216-48 097305 097505-D 097218-48 097306 097506 1. Basic Information: **NFPA** Manufacturer: WILLIAM H. HARVEY COMPANY Address: 4334 SOUTH 67TH STREET City, ST Zip: OMAHA, NE 68117-1019 Health Reactivity 0 Last Update: 7/8/2002 **Chemical State:** Solid Liquid Gas **Chemical Type:** Pure Mixture Health Flammability Reactivity Pers. Protection

| CAS No. | Chemical Name | % Range | EHS | NTP | IARC | SUB Z | SARA 313 | OSHA PEL | ACGIH TLV | Other Limits |
|--------------------------------|----------------------------|---------|-----|-----|------|--------|-------------|-------------|--------------|-----------------|
| 12125029 | AMMONIUM CHLORIDE | NI | | | | | X | 10 MG/M: | 20 | NI |
| 8009038 | PETROLATUM | NI | | | | | | 5 MG/M3 | NI | NI |
| 7646857 | ZINC CHLORIDE | NI | | | | | X | 1 MG/M3 | 2 MG/M3 | NI |
| II. Hazardo | us Identification: | | | | | | | | | |
| Hazard Category: Acute Chronic | | Fire | | | | Pressu | re | | Reactiv | /e |
| Hazardous I | dentification Information: | | | | | | | | | |

Route(s) of Entry:

INHALATION, INGESTION AND SKIN

Health Hazards (Acute and Chronic):

IRRITATION MAY RESULT FROM CONTACT. LONG CONTACT MAY CAUSE DAMAGE. MUTAGENIC IN LAB ANIMALS. HEALTH STUDIES HAVE SHOWN THAT POTENTIAL HEALTH RISKS MAY VARY BY INDIVIDUAL. ALWAYS MINIMIZE EXPOSURE AS A PRECAUTION.

Signs and Symptoms:

Page: 2 of 4 Date Printed: 8/22/2002

MSDS - Material Safety Data Sheet

Product Name: Soldering Paste

MSDS No.: 097250

EYES: REDNESS, BURNING TEARING, BLURRED VISION

SKIN: REDNESS, BURNING, RASH, DRYNESS

INHALATION: HEADACHE, DIZZINESS, DIFFICULTY BREATHING

INGESTION: NAUSEA, VOMITING, CRAMPS

Medical Conditions Generally Aggravated by Exposure:

SKIN AND RESPIRATORY CONDITIONS

Emergency and First Aid Procedures:

EMERGENCY FIRST AID CALL: 1-303-623-5716 COLLECT

EYES: FLUSH IMMEDIATELY WITH WATER FOR AT LEAST 15 MINUTES; SEEK MEDICAL ATTENTION

SKIN: FLUSH WITH WATER IMMEDIATELY; SEEK MEDICAL ATTENTION.

INHALATION: REMOVE TO FRESH AIR; SUPPORT RESPIRATION IF REQUIRED; CALL A PHYSICIAN

INGESTION: DRINK LARGE AMOUNTS OF WATER; SEEK MEDICAL ATTENTION

Other Health Warnings:

AVOID CONTACT. KEEP OUT OF REACH OF CHILDREN AND PETS!

V. Fire Fighting Measures:

Flash Point: 490 F DEG Lower Explosive Limit: NI Upper Explosive Limit:

Fire Extinguishing Media: DRY CHEMICAL

Special Fire Fighting Procedures:

TREAT AS GAS FIRE. FIRE FIGHTERS SHOULD USE SELF-CONTAINED BREATHING APPARATUS TO PROTECT AGAINST SMOKE INHALATION

Unusual Fire and Explosion:

ΝI

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

FLUSH INTO A CHEMICAL SEWER OR SOAK UP WITH A SUITABLE ABSORBANT

VII. Handling and Storage:

Precautions to be Taken:

KEEP CONTAINER CLOSED WHEN NOT IN USE

Other Precautions:

AVOID CONTACT. KEEP OUT OF REACH OF CHILDREN AND PETS!

VIII. Exposure Controls/Personal Protection:

Ventilitation Requirements:

LOCAL EXHAUST; MECHANICAL (GENERAL) OK

Personal Protective Equipment:

RUBBER OR PLASTIC PROTECTIVE GLOVES, FACE SHIELD OR GOGGLES, OTHER PROTECTIVE EQUIPMENT OR CLOTHING AS REQUIRED TO AVOID CONTACT WITH SKIN. WASH AFTER USE; FOLLOW GOOD INDUSTRIAL HYGIENIC PRACTICES; LAUNDER SOILED CLOTHING BEFORE RE-USE.

Page: 3 of 4 Date Printed: 8/22/2002

MSDS - Material Safety Data Sheet

Product Name: Soldering Paste

MSDS No.: 097250

IX. Physical and Chemical Properties:

Boiling Point: NI Melting Point: 82 F DE Evaporation Rate: <1

Vapor Pressure (mm Hg.): NI Vapor Density (AIR = 1): NI

Solubility In Water: SLIGHTLY

Apprearance and Odor: YELLOW SOLID; PETROLEUM ODOR

Other Information:

X. Stability and Reactivity:

Stability:

STABLE

Incompatibility (Materials to Avoid):

STRONG BASES

Decomposition/By Products:

AMMONIA

Hazardous Polymerization:

WILL NOT OCCUR

XL Toxicological Information:

NDA

XII. Ecological Information:

NDA

XIII. Disposal Considerations:

DISPOSE OF IN A LANDFILL IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS

XIV. Transport Information:

TRANSPORATION INFORMATION:

DOT PROPER SHIPPING NAME: SOLDERING PASTE

DOT LABEL: NOT REGULATED

DOT NUMBER: N/A UN NUMBER: N/A MCO CLASS: N/A

DOT HAZARD CLASSIFICATION: N/A

XV. Regulatory Information:

NDA

Page: 4 of 4 Date Printed: 8/22/2002

MSDS - Material Safety Data Sheet

Product Name: Soldering Paste

MSDS No.: 097250

XVI. Other Information:

ABBREVIATIONS:

N/A = NOT APPLICABLE N/I = NONE INDICATED NDA = NO DATA AVAILABLE N/E = NOT ESTABLISHED C = CELSIUS DEGREES F = FAHRENHEIT DEGREES

DISCLAIMER:

THE INFORMATION HEREIN HAS BEEN COMPILED FROM SOURCES BELIEVED TO BE RELIABLE, UP-TO-DATE, AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, WILLIAM H. HARVEY COMPANY CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE WARRANTIES, NOR ASSUMES ANY LIABILITY FOR ITS USES.